



A910S

ESSENTIAL Smart Mobile



Food & Beverage



Fashion & Retail



Transportation



Paydroid Powered
by Android 10



PCI PTS 6.x
SRED



5" HD Display



2MP
Rear-Facing
Camera



Advanced
Connectivity

SMARTPOS

www.paxtech.com.au





















MAXSTORE

A910S

A910S-0AW-RD6-21EP

Android
Mobile

SPECIFICATIONS

	Operating System	Paydroid Powered by Android 10
	Processor	AP (ARM Cortex A53) + SP (ARM)
	Memory	8GB eMMC Flash + 1GB DDR3 RAM Extended microSD card slot up to 128GB
	Card Readers	Chip & PIN Contactless Magnetic Stripe
	Cameras	2MP Rear-Facing camera with flashlight
	Displays	5" IPS HD 720 x 1280 Pixels Multi-Point Capacitive Touch Screen
	Comms Configurations	4G + Wi-Fi® (2.4 & 5GHz) + Bluetooth® 5.0 GPS (together with 4G)
	Battery	2600mAh 7.2V, 18.72Wh, (equal to 5200mAh/3.6V)
	Printer	40 Lines/sec Paper roll outer diameter: 40mm
	SIM / SAM	1 micro SIM + 1 Mini SIM + 1 PSAM
	Positioning	AGPS GPS GLONASS BEIDOU
	Keys / Buttons	3 Keys: Power ON/OFF Volume+ Volume-
	Audio	1 Buzzer 1 Speaker 1 microphone
	Ports	1 Type C USB OTG
	Adapter	Input: 100 - 240V AC, 50Hz / 60Hz Output: 5.0V DC, 2.0A
	Accessories	Charging Base (B910S_RTX-BC) Charging + Wireless Communication Base (B910S_RTX-BE)
	Physical	172.8 x 78 x 62 mm 361g (Including battery)
	Environmental	0°C ~ 45°C (32°F ~ 113°F) Operating Temperature -20°C ~ 70°C (-4°F ~ 158°F) Storage Temperature 5% ~ 95% Relative Humidity, Non-Condensing
	Certifications	PCI PTS 6.x SRED EMV L1 & L2 EMV Contactless L1 Visa payWave MasterCard Contactless UPI qUICS Amex ExpressPay Discover D-PAS JCB J/Speedy Interac Flash TQM CE RoHS BQB ABECS Anatel BIS CB

